

ECK40

电子校准件

Electronic Calibrator

Technical Specifications



文件编号:ITENEST-WI-YX-111/A

ECK40 Specification

MEASUREMENT RANGE	
Frequency Range	100kHz to 40GHz
Number of Ports	2 ports
Port Connector Type	2.92mm, Female
Port Impedance	50Ω
Damage RF Level	20dBm
Max DC Level	10V
GENERAL AND ENVIRONMENT	
Operating Temperature	+20°C to +30°C (Recommend)
Operating Humidity	20% to 80% at wet bulb temperature <+29°C (non-condensation)
Storage Temperature	-10°C to +50°C
Storage Humidity	20% to 90% at wet bulb temperature <+40°C (non-condensation)
Dimensions	50mm W x 120mm L x 31mm H
Weight	<350g
USB Port	Type B-receptacle, provide connection to VNA
Indicator Light	Red: Preheat Green: Ready
Power Consumption	<5W
Recommended Calibration Cycle	12 months





深圳市极致汇仪科技有限公司 SHENZHEN ITEST TECHNOLOGY CO.,LTD

地址：深圳市宝安区新安街道兴东社区67区留芳路6号庭威产业园1号楼5C
电话：+86-755-2153 5646
传真：+86-755-2640 5551
销售部邮箱：wtsales@itenest.com
技术服务邮箱：support@itenest.com
www.itenest.com

台湾办事处

地址：新北市土城区承天路33号8楼
电话：+886-2-2269 2007
传真：+886-2-2269 2036

西南办事处

地址：成都市武侯区武兴五路77号智领大厦
二单元2楼201室
电话：+86 139 8070 7051

华东办事处

地址：苏州市高新区邓尉路9号润捷广场北楼803室
电话：+86 180 6193 4935

华中办事处

地址：武汉市江夏区滨湖路佩尔中心B座11楼
电话：+86 186 0714 9336

